




M52 - SPY 52 92745 MDL

REFERENCE 24434 9230 FBR

AVAILABLE IN
BLACK 24434 9230 B
FLEMISH BRONZE 24434 9230 FBR
FLEMISH GOLD 24434 9230 FG
GOLD COLOURED 24434 9230 GC
WHITE 24434 9230 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCLLED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 30° available
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	898lm // 14,3W // 63lm/W

Remarks
[Take a look at our MAGNETIC PROFILES movie](#)

Requirements
SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Options
DIMMABLE MODULATOR

Accessories
HONEYCOMB 42
SPREAD LENS 42

DELTALIGHT

M52 - SPY 52 92745 MDL

24434 9230 FBR

LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual : [24434_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

13

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

13

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

13

Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures







of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current





DELTALIGHT

M52 - SPY 52 92745 MDL

24434 9230 FBR

	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	7	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	16	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	7	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	14	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			


Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐


DELTALIGHT

M52 - SPY 52 92745 MDL

24434 9230 FBR

 Ø42	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐
---	---	--------------------------





Finish your product

 Ø49	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens

 Ø45	19810 0180 SPY 52 REFLECTOR 20°	☐
 Ø45	19810 0190 SPY 52 REFLECTOR 45°	☐
 Ø45	19810 0240 SPY 52 REFLECTOR 30°	☐

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile		Available Colours
	420 52 10 00 SPM52 - PROFILE 1m	
	420 52 20 00 SPM52 - PROFILE 2m	
	420 52 30 00 SPM52 - PROFILE 3m	
	24413 0000 SPM52 - PROFILE	

Notes: