



PARTOU S IP 93025

25216 9320 W



AVAILABLE IN

NOIR 25216 9320 B

FLEMISH BRONZE 25216 9320 FBR

FLEMISH GOLD 25216 9320 FG

BLANC 25216 9320 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	carré - 76 x 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR FL-25° EXCLLED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	782lm // 9,9W // 79lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM


For detailed installation instructions, please consult the manual : [25216_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

les batteries de secours

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

DELTALIGHT

PARTOU S IP 93025

25216 9320 W


les alimentations led

of Fixtures



web2print_power_supply_info_box

Min current | Max current




300 48 350 ED1

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1 à 10 V

Cutout dimension (mm): 30




300 48 350 ED5

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non dimmable

Cutout dimension (mm): 30




300 48 350 WDL

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45




300 48 500 ED1

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1 à 10 V

Cutout dimension (mm): 30




300 48 500 ED5

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non dimmable

Cutout dimension (mm): 30




300 48 500 WDL

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45



300 90 61

LED POWER SUPPLY MULTI-POWER DIM6










2 | 2

Dimtype: fin de phase ou bouton poussoir

Cutout dimension (mm): 56

PARTOU S IP 93025











25216 9320 W

	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72	3(2) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	2 -	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84	2->6(6) 6(4)	☐
	300 90 91 LED POWER SUPPLY 350mA-DC / 15W Dimtype: non dimmable Cutout dimension (mm): 40	2(1)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	3->4 2->4	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 2	☐

DELTALIGHT






PARTOU S IP 93025

25216 9320 W

	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	3 3	☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 54		
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	3 3	☐
	Dimtype: DALI		
	Cutout dimension (mm): 54		
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	4(4) 4(3)	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 84		
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 3	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 54		
	<u>21012 0258</u> LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 50		
	<u>21012 0268</u> LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 50		
	<u>21012 0278</u> LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 55		
	<u>21012 0288</u> LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->3	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 55		
	<u>21012 0298</u> LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 2	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 48		
	<u>21012 0308</u> LED POWER SUPPLY 350mA / 7,35W DIM8	1	☐
	Dimtype: fin de phase		
	Cutout dimension (mm): 40		

PARTOU S IP 93025

25216 9320 W

	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

Notes: