



HALOSCAN ON 2 MP SOFT 93035 DIM8



23150 9038 W-W

AVAILABLE IN

NOIR-NOIR 23150 9038 B-B

NOIR-COULEUR OR 23150 9038 B-GC

BLANC-BLANC 23150 9038 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS FL-35° INCLDIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm)
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	1246lm // 12W // 105lm/W
LED TECHNICS (LUMINAIRE)	957lm // 13,8W // 69lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23150_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière



Ø72

23110 0040

HALOSCAN LINEAR SPREAD LENS

☐



Ø72

23110 0050 B

HALOSCAN HONEYCOMB B

☐



Ø82

23110 0060 B

HALOSCAN KAP MP B

☐

23110 0060 W

HALOSCAN KAP MP W

☐

Notes: