



ENTERO RD-M IP TW 96530



28416 9020 GC

AVAILABLE IN

BLACK 28416 9020 B

FULL WHITE 28416 9020 FW

GOLD COLOURED 28416 9020 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	145
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.415
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	724lm // 10,4W // 70lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-M MOUNTING SET S2

For detailed installation instructions, please consult the manual : [28416_XXX0_HAND.pdf](#)

DELTALIGHT


ENTERO RD-M IP TW 96530

28416 9020 GC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 28500 0200 - ENTERO RD-M MOUNTING SET S2 Required
 Concrete + plaster	 28500 0200 - ENTERO RD-M MOUNTING SET S2 Required
 Lintel + plaster	 28500 0200 - ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab	 28500 0200 - ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab + plaster	 28500 0200 - ENTERO RD-M MOUNTING SET S2 Required
 Stretched ceiling	-

FINISH YOUR SPECIFICATION


LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current
 21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2

DELTALIGHT

ENTERO RD-M IP TW 96530

28416 9020 GC

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2



Notes: