



ENTERO RD-S TRIMLESS 92745



28425 9230 GC

AVAILABLE IN

NOIR 28425 9230 B

ENTIÈREMENT BLANC 28425 9230 FW

COULEUR OR 28425 9230 GC



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	105
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.235
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-45° EXCLLED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 20° & 30° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-12,4W / CRI>90 (R9: 60) / 2700K / 753-1403lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1076lm // 14,3W // 75lm/W

Remarks

Max.500mA when using accessories

Requirements

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories

ENTERO S HONEYCOMB

ENTERO S LINEAR SPREAD LENS


ENTERO S SPREAD LENS

ENTERO S SOFTENING LENS

For detailed installation instructions, please consult the manual: **28425 XXX0 HAND.pdf**

Ceiling Type	Mounting Kit	
	System ceiling	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Plasterboard	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Stucanet	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Concrete + plaster	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Lintel + plaster	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Hollow-core slab + plaster	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A. Required
	Stretched ceiling	28400 0070 - MOUNTING KIT ENTERO RD-S CSC Required
		28400 0130 - MOUNTING KIT ENTERO RD-S WSC Required
	Ventilation in plasterboard	29810 0100 - MOUNTING KIT SIDE AIR ONLY 1 Required
		29810 0110 - MOUNTING KIT SIDE AIR 105 Required
		29810 0120 - MOUNTING KIT NO AIR 105 Required
	Ventilation in concrete + plaster	29810 0120 - MOUNTING KIT NO AIR 105 Required
		29810 0130 - MOUNTING KIT TOP AIR 105 Required
		29810 0200 - MOUNTING KIT TOP AIR ONLY 1 Required

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27



DELTA LIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 GC











21032 0270 W

EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

les alimentations led		# of Fixtures
web2print_power_supply_info_box		Min current Max current
22 17 90	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2
74 37 20	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2
22 17 90	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2
74 37 20	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2
22 17 90	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2
74 37 20	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2
22 17 90	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2
74 37 20	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2











ENTERO RD-S TRIMLESS 92745

28425 9230 GC

	300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2	☐
	300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 Dimtype: DALI Cutout dimension (mm): 45	2	☐
	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL Dimtype: non dimmable Cutout dimension (mm): 30	2	☐
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 45	2	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: fin de phase ou bouton poussoir Cutout dimension (mm): 56	2 2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82	4(4) 4(4) 4(3)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 72	2(2) 2(1) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	2 - 2	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	2(2) 2(1) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84	2->6(6) 6(4) 4(3)	☐











ENTERO RD-S TRIMLESS 92745

28425 9230 GC

	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	3(2) 2(1) 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) 2(1) 1(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	3->4 2->4 2->4	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 2 2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3 3 2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 3 3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4) 3(3) 3(3)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3 3 2	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 0 0	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 1	☐

ENTERO RD-S TRIMLESS 92745


28425 9230 GC

	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->3 2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 2 1	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(2)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

DELTALIGHT

ENTERO RD-S TRIMLESS 92745


28425 9230 GC

	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2 ☐
Dimtype: DALI		
Cutout dimension (mm): 30		



kit de montage

	28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.	☐
Cutout dimension (mm): 105		
	28500 0220 MOUNTING KIT DEEP ENTERO RD-S TRIMLESS	☐
Cutout dimension (mm): 133		

kit de montage plafond tendu

	28400 0070 MOUNTING KIT ENTERO RD-S CSC	☐
	28400 0130 MOUNTING KIT ENTERO RD-S WSC	☐

kit de montage - side air + light


	29810 0100 MOUNTING KIT SIDE AIR ONLY 1	☐
Cutout dimension (mm): 168		
	29810 0110 MOUNTING KIT SIDE AIR 105	☐
Cutout dimension (mm): 168		

DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 GC

kit de montage - top air + light




29810 0130 MOUNTING KIT TOP AIR 105

Cutout dimension (mm): 135

☐

kit de montage - top air only




29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135

☐

kit de montage - no air




29810 0120 MOUNTING KIT NO AIR 105


Cutout dimension (mm): 168

☐


modifier les dispositifs de lumière




28500 0010 ENTERO S LINEAR SPREAD LENS

☐

28500 0020 ENTERO S SPREAD LENS

☐

28500 0030 ENTERO S SOFTENING LENS

☐


28500 0040 ENTERO S GLASS SBL

☐


DELTALIGHT

ENTERO RD-S TRIMLESS 92745

28425 9230 GC




28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

☐

28500 0060 B ENTERO S HONEYCOMB DOUBLE USE B

☐

Réflecteur / lentille remplaçable



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: