



## OML50 - LED ARRAY D HE 1312mm EM-3H 940 DIM5

31219 9405

 [Bekijk op website](#)



Algemene info	
<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	1.4
<b>INFO</b>	CLUSTER DOWN: 2898lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%
Elektrische info	
<b>INGANGSSPANNING</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	D
<b>CERTIFICATEN</b>	EPD, RCM
Info lichtbron	
<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	LED cluster 22,3W / CRI>90 (R9: 50) / 4000K / 3802lm
<b>TM-30-15 WAARDEN</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	3802lm // 22,3W // 171lm/W

### Opties

WIRELESS CONTROL DIM5

Notes: