



M26L - SPY 391 SOFT 93040 MDL

23437 9030 BRA

AVAILABLE IN

NOIR 23437 9030 B

ALU BROSSÉ 23437 9030 BRA

ANTHRACITE BROSSÉ 23437 9030 BRAT

CUIVRE BROSSÉ 23437 9030 BRCU

OR BROSSÉ 23437 9030 BRG

BRONZE VIEUX BROSSÉ 23437 9030 BROB


FLEMISH BRONZE 23437 9030 FBR

FLEMISH GOLD 23437 9030 FG

COULEUR OR 23437 9030 GC

NOIR PIANO 23437 9030 PB

BLANC 23437 9030 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 85° inclinable, 360° rotatif
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = dimmable 1 à 10 V ou DALI ou bouton poussoir
ENERGY CLASS	F
CERTIFICATION	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements

SPY 39 TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M26L - SPY 391 SOFT 93040 MDL

23437 9030 BRA

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

le cable d'alimentation

of Fixtures

 web2print_power_supply_info_box

Min current | Max current



21032 0030

SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = dimmable sans fil

SMART 48

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 90 011

SMART 48 MODULATOR DIM9

16

Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 012

SMART 48 MODULATOR WD

16


Dimtype: WDL = dimmable sans fil

les alimentations led

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 89 48 100

LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non dimmable



300 89 48 240

LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non dimmable


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL



23437 9030 BRA

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 40		

Terminez votre produit

	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FG SPY 39 TUBE FG	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	23358 0000 SLM26L - PROFILE 
	23358 0010 SLM26L - PROFILE 1m 


DELTALIGHT

M26L - SPY 391 SOFT 93040 MDL

23437 9030 BRA



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: