



OML50 - LED ARRAY DU HE 1312mm 940

31041 9400

 [Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.3
INFO	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 22,3W / CRI>90 (R9: 50) / 4000K / 3802lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3802lm // 22,3W // 171lm/W UP: 2643lm // 16,3W // 162lm/W

Notes: