MONTUR









With Montur, Deltalight offers a highly original interpretation of an archetypical concept: a light source that is contained within the framing of a 3D rectangular or circular shape. The Montur is available in indoor and outdoor versions, as a ground, wall or ceiling fixture, with LED clusters or filament-LED lamps with a rustic look. The series integrates beautifully in both country-classic and contemporary homes, and is suitable for hotels and public buildings as well.

Specification	
Installation Method:	4" junction box -or- ½" EMT conduit
Adjustability:	Fixed
Rating:	Damp -or- Wet, *see Ordering below*

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
*Montur Small/Medium Std Power (SP):	6.3W
*Montur Small/Medium E26:	40W max - E26 medium base 120V
*Montur Large E26:	2 x 40W max - E26 medium base 120V

Delivered Lumens	**2700K**	**3000K**
Montur Small SP:	526	555
Montur Medium SP:	439	459

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering

SEE NEXT PAGE FOR MEDIUM AND LARGE SIZE

Example: MTRSPG6-ENA-B-ONNANA

Luminaire	Size	Style	Rating	CCT	Power*	Finish	Installation	Application	Controls***
MTR MONTUR	**S** Small 5 15/16" cube	**PG** Pressed Glass with frosted interior, enclosed	**6** Wet for exterior use	**27** 2700K **30** 3000K	**SP** Standard Power	**A** Alu Grey **B** Black **FBR** Flemish Bronze **N** Anthracite **W** White	**ON** Surface mounted to 4" junction box M or 1/2" EMT install	**INC** Integral Power Supply	**ND-120** Non-dim 120V
	O Open	**2** Damp for interior use	**E** E26 medium base	**NA** Lamp not included, 40w max	**B** Black **FBR** Flemish Bronze **FG** Flemish Gold	**ON** Surface mounted to 4" junction box M or 1/2" EMT install	**NA** 120V	**NA** Dimmability depends on lamp used	

*** Contact factory for additional dimming options.

Related Products

Montur (bollards), Walker (wall & bollards)

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER


Example: MTRMCG6-ENA-B-ONNANA

Luminaire	Size	Style	Rating	CCT	Power*	Finish	Installation	Application	Controls***
MTR MONTUR	**M** Medium $6^{5}/_{16}$" x $9^{7}/_{16}$" x 4"	**PG** Pressed Glass with frosted interior, enclosed	**6** Wet for exterior use	**27** 2700K **30** 3000K	**SP** Standard Power	**A** Alu Grey **B** Black **FBR** Flemish Bronze **N** Anthracite **W** White	**ON** Surface mounted to 4" junction box M or 1/2" EMT install	**INC** Integral Power Supply	**ND-120** Non-dim 120V
		CG Clear glass, enclosed	**6** Wet for exterior use	**E** E26 medium base	**NA** Lamp not included, 40w max	**B** Black	**ON** Surface mounted to 4" junction box M or 1/2" EMT install	**NA** 120V	**NA** Dimmability depends on lamp used
		O Open	**2** Damp for interior use	**E** E26 medium base	**NA** Lamp notincluded, 40w max	**B** Black **FBR** Flemish Bronze **FG** Flemish Gold			
	L Large $5^{1}/_{2}$" x $19^{1}/_{16}$" x $5^{1}/_{2}$"	**O** Open	**2** Damp for interior use	**E** E26 medium base x2	**NA** Lamp not included, 2x 40w max	**B** Black			

*** Contact factory for additional dimming options.


Finish Options

MONTUR SMALL STD POWER (WET)




ALU GREY



BLACK


FLEMISH BRONZE


ANTHRACITE


WHITE

MONTUR SMALL E26 (DAMP)





BLACK


FLEMISH BRONZE


FLEMISH GOLD

MONTUR MEDIUM STD POWER (WET)




ALU GREY


BLACK


FLEMISH BRONZE



ANTHRACITE


WHITE

DELTALIGHT


Finish Options (cont.)

MONTUR MEDIUM E26 (WET)




BLACK

MONTUR MEDIUM E26 (DAMP)





BLACK


FLEMISH BRONZE


FLEMISH GOLD


MONTUR LARGE E26 (DAMP)





BLACK

Photometric Data

MONTUR SMALL



MONTUR MEDIUM



Driver Options

ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.6
- Efficiency @ Full Load ≥77
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.