



MONTUR



With Montur, Delta Light offers a highly original interpretation of an archetypal concept: a light source that is contained within the framing of a 3D rectangular or circular shape. The Montur is available in indoor and outdoor versions, as a ground, wall or ceiling fixture, with LED clusters or filament-LED lamps with a rustic look. The series integrates beautifully in both country-classic and contemporary homes, and is suitable for hotels and public buildings as well.

Specification	
Installation Method:	1/2" EMT or 4" J-Box
Adjustability:	Fixed
Rating:	IP20 & IP65, <i>see Ordering below</i>

Performance	
CRI:	90
*Montur S/M SP (LED)	6.3W
*Montur S/M E26:	40W max - E26 Medium Base 120V
*Montur L E26:	2 x 40W max - E26 Medium Base 120V

Delivered Lumens	2700K	3000K
Montur M SP (LED):	439Lm	459Lm
Montur S SP (LED):	526Lm	555Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MTR6M-SP27-ND-120-PG-B-SF

Luminaire	Rating	Size	Power*	CCT	Controls	Style	Finish	Installation	
MTR MONTUR	6 IP65 for exterior use	S Small 5 ¹⁵ / ₁₆ " cube	SP Standard Power	27 2700K	ND-120 Non-dim 120V	PG Frosted/pressed glass enclosed	A Alu Grey B Black FBRX Flemish Bronze N Anthracite W White	ON Surface mounted to 4" junction box M or 1/2" EMT install	
		M Medium 6 ⁵ / ₁₆ " x 9 ⁷ / ₁₆ " x 4"	SP Standard Power	30 3000K					
			E E26	NA Lamp not included	NA 120V	CG Clear glass enclosed			
	2 IP20 for exterior use	S Small 5 ¹⁵ / ₁₆ " cube	E E26	NA Lamp not included	NA 120V	O Open	B Black FBRX Flemish Bronze FG Flemish Gold		
		M Medium 6 ⁵ / ₁₆ " x 9 ⁷ / ₁₆ " x 4"							
		L ¹ Large 5 ¹ / ₂ " x 19 ¹ / ₁₆ " x 5 ¹ / ₂ "							

¹ Only available with Finish B.
*** Contact factory for additional dimming options.

Related Products

Montur (bollards), Walker (wall & bollards)

DELTALIGHT


www.deltalight.com





Finish Options


MONTUR M SP (LED) IP65



ALU GREY



BLACK



FLEMISH BRONZE




ANTHRACITE




WHITE


MONTUR S SP (LED) IP65



ALU GREY



BLACK



FLEMISH BRONZE




ANTHRACITE




WHITE

MONTUR M E26 IP65




BLACK


MONTUR S E26 IP20



BLACK




FLEMISH BRONZE




FLEMISH GOLD

MONTUR M E26 IP20



BLACK




FLEMISH BRONZE



FLEMISH GOLD

MONTUR L E26 IP20




DELTALIGHT

www.deltalight.com




Photometric Data

MONTUR M



MONTUR S



Driver Options

ND

- Dimming Control NON DIMMABLE
- Power Factor @ Full Load >0.6
- Efficiency @ Full Load ≥77
- THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.