DELTALIGHT



NOCTA SQ85 DOWN-UP SP 930

REFERENCE 30121 9300 W

AVAILABLE IN
ALU GREY 30121 9300 A
BLACK 30121 9300 B
FLEMISH BRONZE OUTDOOR 30121 9300 FBRX
ANTHRACITE 30121 9300 N
WHITE 30121 9300 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x LENS INCL.LED POWER SUPPLY 700 mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm)
TM-30 VALUES	Rf: 91 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	960lm // 8W // 120lm/W
LED TECHNICS (LUMINAIRE)	788lm // 9,2W // 86lm/W

For detailed installation instructions, please consult the manual : **30121_XXX0_HAND.pdf**

DELTALIGHT

NOCTA SQ85 DOWN-UP SP 930

30121 9300 W

Notes: