





ENTERO SQ-S IP TW 96545

REFERENCE 28508 9030 B

AVAILABLE IN
BLACK 28508 9030 B
FULL WHITE 28508 9030 FW
GOLD COLOURED 28508 9030 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	115
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.25
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	711lm // 10,4W // 69lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW


For detailed installation instructions, please consult the manual : [28508_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5	2 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 85	

Replaceable reflector / lens		
	<u>19810 0180</u> SPY 52 REFLECTOR 20°	☐

	19810 0190 SPY 52 REFLECTOR 45°	☐
--	--	--------------------------

DELTALIGHT

ENTERO SQ-S IP TW 96545

28508 9030 B



19810 0240 SPY 52 REFLECTOR 30°



Notes: