





M26L - SPY 39 WALLWASH 930 DIM5

23434 9305 BROB

AVAILABLE IN

BLACK 23434 9305 B
BRUSHED ALU 23434 9305 BRA
BRUSHED ANTHRACITE 23434 9305 BRAT
BRUSHED COPPER 23434 9305 BRCU
BRUSHED GOLD 23434 9305 BRG
BRUSHED OLD BRONZE 23434 9305 BROB
FLEMISH BRONZE 23434 9305 FBR
FLEMISH GOLD 23434 9305 FG
GOLD COLOURED 23434 9305 GC
WHITE 23434 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS EXCLLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	431lm // 6,7W // 65lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23434_XXX5_HAND.pdf](#)

M26L - SPY 39 WALLWASH 930 DIM5

23434 9305 BROB

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	10	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	24	
1729830 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	10	
2239230 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	20	


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
3226 23358 0000 SLM26L - PROFILE	
3226 23358 0010 SLM26L - PROFILE 1m	
3226 23358 0020 SLM26L - PROFILE 2m	

DELTALIGHT

M26L - SPY 39 WALLWASH 930 DIM5

23434 9305 BROB



23358 0030 SLM26L - PROFILE 3m



Notes: