



OML50 - LED ARRAY DU HO 1312mm EM-3H 930

31221 9300



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.7
INFO	CLUSTER DOWN: 3863lm/m CLUSTER UP: 2663lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 3000K / 5069lm UP: LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 5069lm // 32,6W // 155lm/W UP: 3494lm // 24,2W // 145lm/W

Notes: