



SUPERLOOP MDL



Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Superloop is also available in a round or squared shapes with a Delta Light custom engineered 48V low voltage track on the inside. This allows you to position and move light modules all around, offering maximum flexibility and allowing you to meet any need of the project. The modules enable you to move from subtle functionality to very expressive or timeless elegance.

Specification	
Installation Method:	4" junction box
Adjustability:	Fixed
Rating:	Damp (EU IP20)
*Power Capacity	
Medium Power (MP):	50W max, 48V
³ Remote Power Supply Capacity (# luminaires) MP:	D1-UNV min1-max1
High Power (HP):	90W max, 48V
³ Remote Power Supply Capacity (# luminaires) HP:	D1-UNV min1-max1
Compatible Luminaires	
Superloop Fix 40 Down MDL:	4.7W
Superloop Fix 40 Down-Up MDL:	7.1W
Superloop Fix 45 Down MDL:	9W
Superloop Spy 52 MDL:	10W
Superloop Spy 66 MDL:	20W
Superloop Spy Focus MP MDL:	10W
Superloop Spy Focus XP MDL:	20W
Superloop Vizir/Hedra LP MDL:	6.7W
Superloop Vizir/Hedra MP MDL:	6.9W
Superloop XY180 MDL:	10W

Ordering

SEE NEXT PAGE FOR SQUARED SHAPE

Example: SLP-MDLR30NA-HP-FBR-B-HCPSRMTD1-UNV

Luminaire	Shape	Size	Acoustic Panel	Power*	Finish	Hardware Finish ²	Type	Installation	Application	Controls
SLP-MDL ¹ SUPERLOOP MDL	R Round	07 695mm / 27 ³ / ₈ "	LG Light Grey	MP Medium Power	B Black	B Black	HC Horizontal, 9' cables, 3 suspension points	NA Includes surface canopy	PB Power Box canopy	ND-120 Non-dim 120V
		09 924mm / 36 ³ / ₈ "	DG Dark Grey	HP High Power	FBR Flemish Bronze			PR Round coverplate for 4" junction box	RMT ³ Remote Power Supply	D1-UNV 0-10V dim 120-277V
		12 1191mm / 46 ¹ / ₈ "	NA Not Applicable		FG Flemish Gold	W White	HC Horizontal, 9' cable suspended ⁴	PS Square coverplate for 4" junction box		
		17 1688mm / 66 ⁷ / ₈ "		MP Medium Power	B Black	B Black	HC Horizontal, 9' cable suspended ⁴	NA Includes surface canopy	PB Power Box canopy	ND-120 Non-dim 120V
		20 2015mm / 79 ⁵ / ₁₆ "			FBR Flemish Bronze					
		25 2493mm / 98 ¹ / ₈ "			FG Flemish Gold					
		30 2971mm / 117								
		35 3449mm / 131 ⁷ / ₈ "								
		40 4023mm / 158 ³ / ₈ "								
		50 4943mm / 194 ¹ / ₈ "								

¹ Luminaire modules are required and specified separately.
² Applies to PS & PR (coverplate) or PB (power box).

³ Remote power supply capacity noted in table above.
⁴ See Finish Options section for suspension quantity.



Ordering (cont.)

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SLP-MDLS11NA-MP-B-B-HCNAPBND-120

Luminaire	Shape	Size	Acoustic Panel	Power*	Finish	Hardware Finish ²	Type	Installation	Application	Controls
SLP-MDL ¹ SUPERLOOP MDL	S Squared	06 600mm x 600mm 235/8" x 235/8"	NA Not Applicable	MP Medium Power	B Black	B Black	HC Horizontal, 9' cables, 4 suspension points	NA Includes surface canopy	PB Power Box canopy	ND-120 Non-dim 120V
		09 900mm x 900mm 357/16" x 357/16"		HP High Power	B Black	B Black	HC Horizontal, 9' cables, 4 suspension points	PR Round coverplate for 4" junction box	RMT ³ Remote Power Supply	D1-UNV 0-10V dim 120 277V
		11 1100mm x 250mm 435/16" x 913/16"					HC Horizontal, 9' cables, 4 suspension points			
		17 1693mm x 250mm 665/8" x 913/16"				W White	HC Horizontal, 9' cables, 4 suspension points	PS Square coverplate for 4" junction box		

¹ Luminaire modules are required and specified separately.² Applies to PS & PR (coverplate) or PB (power box).³ Remote power supply capacity noted in table on Page 1.

Related Products

Superloop, Shiftline M, Splitline M











Finish Options

SUPERLOOP MDL R07


SUPERLOOP MDL R09

SUPERLOOP MDL R12


SUPERLOOP MDL R17

SUPERLOOP
MDL R20SUPERLOOP
MDL R25SUPERLOOP
MDL R30SUPERLOOP
MDL R35SUPERLOOP
MDL R40SUPERLOOP
MDL R50Constructed of
2 segments; each
segment has 2 suspension
cables + 1 powerfeedConstructed of
3 segments; each
segment has 2 suspension
cables + 1 powerfeedConstructed of
3 segments; each
segment has 2 suspension
cables + 1 powerfeedConstructed of
4 segments; each
segment has 2 suspension
cables + 1 powerfeedConstructed of
4 segments; each
segment has 2 suspension
cables + 1 powerfeedConstructed of
5 segments; each
segment has 2 suspension
cables + 1 powerfeed

FINISHES - ROUND





BLACK



FLEMISH BRONZE



FLEMISH GOLD

ACOUSTIC PANEL
DARK GREYACOUSTIC PANEL
LIGHT GREY





DELTALIGHT

www.deltalight.com





SUPERLOOP Ver 11 12.09.25

2



Finish Options (cont.)

SUPERLOOP MDL S06	SUPERLOOP MDL S09	SUPERLOOP MDL S11	SUPERLOOP MDL S17
			
			

Installation Options

REMOTE DRIVER	PR - COVERPLATE R 104	PS - COVERPLATE S 103
A: 9"-5/16 x B: 2"-1/2 x C: 1"-5/16 A: 252mm x B: 63.6mm x C: 34mm  • For Remote application • ETL Listed • Damp rated 	 BLACK or WHITE Requires 4" junction box	 BLACK or WHITE Requires 4" junction box

PB - POWER BOX

		
POWER BOX H	POWER BOX L	BLACK
Used with POWER HP	Used with POWER MP	

Driver Options

D1
• Dimming Control 0-10V / DALI • Dimming Range 1-100% • Dim to off yes • Power Factor @ Full Load >0.95 • Efficiency @ Full Load ≥90 • THD @ Full Load <10%
ND
• Dimming Control NON DIMMABLE • Power Factor @ Full Load >0.95 • Efficiency @ Full Load ≥90 • THD @ Full Load <10%

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.