





SUPERLOOP VR 70 SBL 927

REFERENCE 321 407 92 B

AVAILABLE IN
BLACK 321 407 92 B
FLEMISH BRONZE 321 407 92 FBR
FLEMISH GOLD 321 407 92 FG
WHITE 321 407 92 W






[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 500-700mA-DC INCL.1 x SUSPENSION TUBE 0.5m
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,2-29,2W / CRI>90 (R9: 59) / 2700K / 2916-3870lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3870lm // 29,2W // 132lm/W
LED TECHNICS (LUMINAIRE)	2325lm // 33,6W // 69lm/W
Requirements	
LED POWER SUPPLY 500 / 700mA-DC DIM	

For detailed installation instructions, please consult the manual : [321_407_92_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
<div><div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		Min current Max current
<div><div></div><div><div>300 90 127</div><div>LED POWER SUPPLY 500mA-DC / 27W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 54</div></div></div>	1	<input type="text"/>
<div><div></div><div><div>300 90 128</div><div>LED POWER SUPPLY 700mA-DC / 36W DIM1</div><div>Dimtype: 1-10V</div><div>Cutout dimension (mm): 54</div></div></div>	1	<input type="text"/>
<div><div></div><div><div>300 90 131</div><div>LED POWER SUPPLY 700mA-DC / 38W DIM5</div><div>Dimtype: DALI</div><div>Cutout dimension (mm): 54</div></div></div>	1	<input type="text"/>

Notes: