
DELTALIGHT




M26L - SPY 391 93020 DIM5

REFERENCE 23259 9325 BRA

AVAILABLE IN
BLACK 23259 9325 B
BRUSHED ALU 23259 9325 BRA
BRUSHED ANTHRACITE 23259 9325 BRAT
BRUSHED COPPER 23259 9325 BRCU
BRUSHED GOLD 23259 9325 BRG
BRUSHED OLD BRONZE 23259 9325 BROB
FLEMISH BRONZE 23259 9325 FBR
FLEMISH GOLD 23259 9325 FG
GOLD COLOURED 23259 9325 GC
PIANO BLACK 23259 9325 PB
WHITE 23259 9325 W







View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

DELTALIGHT

M26L - SPY 391 93020 DIM5

23259 9325 BRA

For detailed installation instructions, please consult the manual : **23259_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




24144 0030 B VISOR 39 B

DELTALIGHT





M26L - SPY 391 93020 DIM5

23259 9325 BRA

Finish your product

	**24144 0010 B**	SPY 39 TUBE B	☐
	24144 0010 FBR	SPY 39 TUBE FBR	☐
	24144 0010 FG	SPY 39 TUBE FG	☐
	24144 0010 GC	SPY 39 TUBE GC	☐
	24144 0010 W	SPY 39 TUBE W	☐
	**24144 0070**	SPY 39 TUBE SBL	☐





COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	**23358 0000** SLM26L - PROFILE	
	**23358 0010** SLM26L - PROFILE 1m	
	**23358 0020** SLM26L - PROFILE 2m	
	**23358 0030** SLM26L - PROFILE 3m	

DELTALIGHT

M26L - SPY 391 93020 DIM5

23259 9325 BRA

SHIFTLINE M35R profile	Available Colours
 **23375 0000** SLM35R - PROFILE	
 **23375 0010** SLM35R - PROFILE 1m	
 **23375 0020** SLM35R - PROFILE 2m	
 **23375 0030** SLM35R - PROFILE 3m	

Notes: