



INFORM SQ F144-3 94067

25523 9420 W-W



AVAILABLE IN

BLACK-BLACK 25523 9420 B-B

BLACK-FLEMISH GOLD 25523 9420 B-FG

WHITE-BLACK 25523 9420 W-B

WHITE-WHITE 25523 9420 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 300/450mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info





LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 4000K / 1670-2416lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2416lm // 16,7W // 144lm/W
LED TECHNICS (LUMINAIRE)	2109lm // 19,2W // 110lm/W

Requirements

INFORM POWER SUPPLY 17W

For detailed installation instructions, please consult the manual : [25523_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 28012130 25510 0050 INFORM POWER SUPPLY 25W Dimtype: non-dimmable	1	
 28012130 25510 0065 INFORM POWER SUPPLY 35W DIM5 Dimtype: DALI	1	
 13120070 25510 0375 INFORM POWER SUPPLY 17W DIM5 Dimtype: DALI	1	
 13120070 25510 0420 INFORM POWER SUPPLY 17W Dimtype: non-dimmable	1	

Notes: