



SUPERLOOP VR 70 SBL 927

321 407 92 FBR



AVAILABLE IN

BLACK 321 407 92 B

FLEMISH BRONZE 321 407 92 FBR

FLEMISH GOLD 321 407 92 FG

WHITE 321 407 92 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 500-700mA-DC INCL.1 x SUSPENSION TUBE 0.5m

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info




LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,2-29,2W / CRI>90 (R9: 59) / 2700K / 2916-3870lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3870lm // 29,2W // 132lm/W
LED TECHNICS (LUMINAIRE)	2325lm // 33,6W // 69lm/W

Requirements

LED POWER SUPPLY 500 / 700mA-DC DIM

For detailed installation instructions, please consult the manual : [321_407_92_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 90 127 LED POWER SUPPLY 500mA-DC / 27W DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1	
 300 90 128 LED POWER SUPPLY 700mA-DC / 36W DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1	
 300 90 131 LED POWER SUPPLY 700mA-DC / 38W DIM5 Dimtype: DALI Cutout dimension (mm): 54	1	

Notes: