





POLESANO W 94070

15931 9430 N-B

AVAILABLE IN

ALU GREY-BLACK 15931 9430 A-B

ANTHRACITE-BLACK 15931 9430 N-B



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP66
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	5.4
ADJUSTABILITY	0° to 55° swiveling, 355° rotatable
INFORMATION	16 x REFLECTOR WFL-70° INCL.LED POWER SUPPLY 900mA-DC $\lambda > 0,9$ Inrush current : 32A - 355 μ s @ 230V-AC Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A)

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, ENEC+, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 62) / 4000K / 5136lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	70°
LED TECHNICS (LIGHT SOURCE)	5136lm // 41,6W // 123lm/W
LED TECHNICS (LUMINAIRE)	3681lm // 47,8W // 77lm/W

Remarks

Take a look at the POLESANO brochure

Options

POLESANO FLOOR BASE

Accessories

HONEYCOMB S105

LINEAR SPREAD LENS S105

DELTALIGHT

POLESANO W 94070

15931 9430 N-B


For detailed installation instructions, please consult the manual : [15931_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




431 03 01 B HONEYCOMB S105 B



431 03 02 LINEAR SPREAD LENS S105

Other



15932 0010 N POLESANO FLOOR BASE N

Notes: