



M20/M26H - MULTINOVA 30 SOFT 930 DIM5



27955 9005 GC

AVAILABLE IN

BLACK 27955 9005 B

GOLD COLOURED 27955 9005 GC

WHITE 27955 9005 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,5W / CRI>90 (R9: 50) / 3000K-1800K / 2188lm
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	2188lm // 14,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	1590lm // 16,7W // 95lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements



LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27955_XXX5_HAND.pdf](#)

M20/M26H - MULTINOVA 30 SOFT 930 DIM5

27955 9005 GC

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		6
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		14
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		6
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		11




COMPATIBLE COMPOSABLES





SHIFTLINE M26H + SBL	Available Colours
 30411 9205 SHIFTLINE M26H + SBL 2m DIM5	
 30411 9305 SHIFTLINE M26H + SBL 2m DIM5	
 30412 9205 SHIFTLINE M26H + SBL 3m DIM5	

DELTALIGHT

M20/M26H - MULTINOVA 30 SOFT 930 DIM5

27955 9005 GC

	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 

SHIFTLINE M26H profile	Available Colours
	23359 0000 SLM26H - PROFILE  
	23359 0010 SLM26H - PROFILE 1m  
	23359 0020 SLM26H - PROFILE 2m          
	23359 0030 SLM26H - PROFILE 3m          

SPLITLINE M20 ST profile	Available Colours
	23397 0000 SPM20 ST - PROFILE  
	23397 0020 SPM20 ST - PROFILE 2m  

DELTALIGHT

M20/M26H - MULTINOVA 30 SOFT 930 DIM5

27955 9005 GC



23397 0030 SPM20 ST - PROFILE 3m



SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: