



DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG

BESCHIKBAAR IN

ZWART 202 144 811 922 B

ALU GEBORSTELD 202 144 811 922 BRA

GEBORSTELD ANTRACIET 202 144 811 922 BRAT

GEBORSTELD BRUIN BRONS 202 144 811 922 BRBB

GEBORSTELD KOPER 202 144 811 922 BRCU

GEBORSTELD GOUD 202 144 811 922 BRG

GEBORSTELD OUD BRONS 202 144 811 922 BROB

CRÈME 202 144 811 922 CR


FLEMISH BRONZE 202 144 811 922 FBR

FLEMISH GOLD 202 144 811 922 FG

GOUD KLEUR 202 144 811 922 GC

PIANO ZWART 202 144 811 922 PB

WIT 202 144 811 922 W



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - Ø KIT
INBOUWDIEPTE (MM)	95
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.3
RICHTBAARHEID	niet richtbaar
INFO	REFLECTOR FL-33° EXCLLED POWER SUPPLY 350-500mA-DC

Elektrische info

KLASSE	III
DIM TYPE	afhankelijk van de te kiezen externe voeding
ENERGIE KLASSE	E
CERTIFICATEN	CB, ENEC, EPD, LCA

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30-15 WAARDEN	Rf: 89 / Rg: 100
SDCM	SDCM1
RISK-GROEP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNIEK (LICHTBRON)	1041lm // 8,6W // 121lm/W
LED TECHNIEK (TOESTEL)	792lm // 9,9W // 80lm/W

Benodigdheden

MOUNTING KIT R82 TRIMLESS O.F.A.

MOUNTING KIT AIR 101

LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

DELTALIGHT

DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG


Voor gedetailleerde montage gegevens, consulteer de handleiding : [202_144_811_XXX_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Ventilation in plasterboard	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
 Ventilation in concrete + plaster	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
 Cold stretched ceiling	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 Warm stretched ceiling	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required

VERVOLLEDIG UW SPECIFICATIE

Noodunits



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Uitsparingsmaat (mm): 27



DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W



LED voedingen

armaturen



armaturen geeft aan hoeveel toestellen op de voeding kunnen worden aangesloten (min -> max). De waarden vóór en na de 'I' komen respectievelijk overeen met de minimale en maximale aanstroom. Waarden tussen haakjes zijn van toepassing op 110V.

Min. stroom | Max. stroom




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

1 ☐

Dimtype: 1-10V

Uitsparingsmaat (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1 ☐

Dimtype: DALI

Uitsparingsmaat (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

1 ☐

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

1 ☐

Dimtype: WDL = draadloos

Uitsparingsmaat (mm): 45




300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1 ☐

Dimtype: 1-10V

Uitsparingsmaat (mm): 30




300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1 ☐

Dimtype: DALI

Uitsparingsmaat (mm): 45




300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1 ☐

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL


1 ☐

Dimtype: WDL = draadloos

Uitsparingsmaat (mm): 45

DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG

	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: net-dimbaar (fase afsnijding) of met drukknop Uitsparingsmaat (mm): 56	2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V of DALI of drukknop Uitsparingsmaat (mm): 82	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V of met drukknop Uitsparingsmaat (mm): 72	2(1) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V of DALI of drukknop	2	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Uitsparingsmaat (mm): 72	2(2) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V of DALI of drukknop Uitsparingsmaat (mm): 84	2->6(6) 6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V of met drukknop Uitsparingsmaat (mm): 55	3(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Uitsparingsmaat (mm): 55	2(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: niet dimbaar Uitsparingsmaat (mm): 90	3->3 2->3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = draadloos Uitsparingsmaat (mm): 84	3(3) 3(3)	☐

DELTALIGHT

DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG



21012 005W

LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3

☐

Dimtype: WDL = draadloos

Uitsparingsmaat (mm): 54



21012 0258


LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

☐

Dimtype: net-dimbaar (fase afsnijding)

Uitsparingsmaat (mm): 50



21012 0278

LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

☐

Dimtype: net-dimbaar (fase afsnijding)

Uitsparingsmaat (mm): 55



21012 0288

LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

☐

Dimtype: net-dimbaar (fase afsnijding)

Uitsparingsmaat (mm): 55



21012 0298

LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

☐

Dimtype: net-dimbaar (fase afsnijding)

Uitsparingsmaat (mm): 48



21012 0480

LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

☐

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 60



21012 0500

LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

☐

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 60



21032 0295

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

☐

Dimtype: DALI

Uitsparingsmaat (mm): 30



21032 0305

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

☐

Dimtype: DALI

Uitsparingsmaat (mm): 30

DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG

Montage kit




15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A.

Uitsparingsmaat (mm): 105

☐

Montage kit spanplafond



15212 0070 MOUNTING KIT R82 TRIMLESS CSC

☐

15212 0150 MOUNTING KIT R82 TRIMLESS WSC

☐

Montage kit - side air + light



29810 0010 MOUNTING KIT SIDE AIR 101

Uitsparingsmaat (mm): 168

☐

Montage kit - top air + light



29810 0210 MOUNTING KIT TOP AIR 101

Uitsparingsmaat (mm): 135

☐

Montage kit - side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Uitsparingsmaat (mm): 168

☐

DELTALIGHT

DEEP RINGO TRIMLESS LED 92733

202 144 811 922 BRG

Montage kit - top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1

Uitsparingsmaat (mm): 135



Montage kit - no air



29810 0050 MOUNTING KIT NO AIR 101

Uitsparingsmaat (mm): 168



Notes: