



HALOSCAN ON 1 MP SOFT 93021 DIM8



23148 9028 W-W

AVAILABLE IN

NOIR-NOIR 23148 9028 B-B

NOIR-COULEUR OR 23148 9028 B-GC

BLANC-BLANC 23148 9028 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS FL-21° INCLDIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	486lm // 6,9W // 70lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23148_XXX8_HAND.pdf](#)




DELTALIGHT

HALOSCAN ON 1 MP SOFT 93021 DIM8

23148 9028 W-W

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière

 Ø72	23110 0040	HALOSCAN LINEAR SPREAD LENS	☐
 Ø72	23110 0050 B	HALOSCAN HONEYCOMB B	☐
 Ø82	23110 0060 B	HALOSCAN KAP MP B	☐
	23110 0060 W	HALOSCAN KAP MP W	☐

Notes: