





INFORM 40 SQ 160 PDS DOWN-UP 94063 DIM5

30722 9435 B-B

AVAILABLE IN

BLACK-BLACK 30722 9435 B-B

WHITE-BLACK 30722 9435 W-B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 4000K / 3642lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101 DOWN: rf: 90 / Rg: 101 UP: rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 3642lm // 24,2W // 151lm/W UP (HO): 3642lm // 24,2W // 151lm/W Or DOWN: 2643lm // 16,3W // 162lm/W UP: 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 2520lm // 27,8W // 91lm/W UP (HO): 2398lm // 27,8W // 86lm/W Or DOWN: 1829lm // 18,7W // 98lm/W UP: 1741lm // 18,7W // 93lm/W

INFORM 40 SQ 160 PDS DOWN-UP 94063 DIM5

30722 9435 B-B


Options

CABLE BASE R/S

For detailed installation instructions, please consult the manual : [30722_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐


203 99 56 W CABLE BASE S W

☐

Other



26510 0010 PDS REMOTE CONTROL

☐

26510 0020 PDS SENSOR PROGRAMMER

☐

DELTALIGHT

INFORM 40 SQ 160 PDS DOWN-UP 94063 DIM5

30722 9435 B-B

Notes: