





SUPERLOOP-SPY 66 92745 MDL

20569 9230 W

AVAILABLE IN

BLACK 20569 9230 B

WHITE 20569 9230 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 30° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1379lm // 19,8W // 70lm/W

Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

For detailed installation instructions, please consult the manual : [20569_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

9

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

9


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

5


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

12

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

5

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SUPERLOOP-SPY 66 92745 MDL

20569 9230 W



22
392
30

21012 0240 LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40

10

☐

Light altering devices



14
Ø57

24611 0150 B HONEYCOMB 57 SINGLE USE B


☐



13
Ø57

24611 0160 GLASS SBL 57


☐



15
Ø57

24611 0170 LINEAR SPREAD LENS 57


☐



13
Ø57

24611 0190 SOFTENING LENS 57


☐



14
Ø57

24611 0200 SPREAD LENS 57

☐



14
Ø57

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



30
Ø63

24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

DELTALIGHT

SUPERLOOP-SPY 66 92745 MDL




20569 9230 W

24611 0100 FG	SPY 66 TUBE FG	☐
24611 0100 GC	SPY 66 TUBE GC	☐
24611 0100 W	SPY 66 TUBE W	☐

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐
	24611 0240 SPY 66 REFLECTOR 45°	☐


COMPATIBLE COMPOSABLES

SUPERLOOP HC MDL	Available Colours
 418 481 07 SUPERLOOP HC 70 MDL	  
 418 481 09 SUPERLOOP HC 90 MDL	  
 418 481 12 SUPERLOOP HC 120 MDL	  

DELTALIGHT

SUPERLOOP-SPY 66 92745 MDL

20569 9230 W




418 481 17 SUPERLOOP HC 170 MDL



SUPERLOOP HC MDL XL

Available Colours




20555 0000 SUPERLOOP HC 200 MDL






20556 0000 SUPERLOOP HC 250 MDL





20557 0000 SUPERLOOP HC 300 MDL





20558 0000 SUPERLOOP HC 350 MDL





20559 0000 SUPERLOOP HC 400 MDL






20560 0000 SUPERLOOP HC 500 MDL




SUPERLOOP PLUS MDL

Available Colours



20564 0000 SUPERLOOP PLUS HC 70 MDL






20565 0000 SUPERLOOP PLUS HC 90 MDL



DELTALIGHT

SUPERLOOP-SPY 66 92745 MDL

20569 9230 W




20566 0000

SUPERLOOP PLUS HC 120 MDL



SUPERLOOP S HC MDL


Available Colours



418 482 106

SUPERLOOP S HC 106 MDL






418 482 109

SUPERLOOP S HC 109 MDL






418 482 211

SUPERLOOP S HC 211 MDL





418 482 217

SUPERLOOP S HC 217 MDL



Notes: