



LOGIC 190 R OK SP 92708

30223 9210 INOX

AVAILABLE IN  
INOX 30223 9210 INOX



 [View on website](#)



| General info                         |                                                                                                                                              |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                             | outdoor                                                                                                                                      |
| INSTALLATION                         | Floor Recessed                                                                                                                               |
| CUTOUT SHAPE/SIZE (MM)               | round - BOX                                                                                                                                  |
| RECESSED DEPTH (MM)                  | 190                                                                                                                                          |
| INGRESS PROTECTION                   | IP67                                                                                                                                         |
| PROTECTION AGAINST MECHANICAL IMPACT | IK10                                                                                                                                         |
| WEIGHT (KG)                          | 2                                                                                                                                            |
| ADJUSTABILITY                        | 0° to 25° swiveling                                                                                                                          |
| INFORMATION                          | 7 x LENS SP-8°<br>INCL.LED POWER SUPPLY 600mA-DC<br>INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m<br>INCL.IP68 CONNECTOR 3P<br>ESG 10mm max.500kg |
| Electrical info                      |                                                                                                                                              |
| ELECTRICAL                           | 220-240V / 50-60Hz                                                                                                                           |
| CLASS                                | I                                                                                                                                            |
| POWER SUPPLY                         | YES                                                                                                                                          |
| DIM TYPE                             | non-dimmable                                                                                                                                 |
| ENERGY CLASS                         | F                                                                                                                                            |
| CERTIFICATES                         | CB, ENEC, EPD, RCM                                                                                                                           |
| Lightsource info                     |                                                                                                                                              |
| LIGHTSOURCE NAME                     | LED                                                                                                                                          |
| LIGHTSOURCE                          | LED cluster 11,9W / CRI>90 (R9: 55) / 2700K / 1339lm                                                                                         |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                                                                                             |
| SDCM                                 | SDCM3                                                                                                                                        |
| RISKGROUP                            | RG2                                                                                                                                          |
| LM80                                 | L80 > 150000                                                                                                                                 |
| BEAMANGLE                            | 8°                                                                                                                                           |
| LED TECHNICS (LIGHT SOURCE)          | 1339lm // 11,9W // 112lm/W                                                                                                                   |
| LED TECHNICS (LUMINAIRE)             | 1051lm // 13,7W // 77lm/W                                                                                                                    |


| Requirements    |
|-----------------|
| LOGIC 190 R BOX |

| Options                            |
|------------------------------------|
| LOGIC 190 ANTI VANDAL SCREWS 2 PCS |

For detailed installation instructions, please consult the manual : [30223\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




**30210 0010** LOGIC 190 R BOX


☐

Cutout dimension (mm): 300 x 230

Waterproof connection parts




**431 99 02** IP68 JUNCTION BOX 4P

☐

**21034 0150** IP68 Y-CONNECTOR 5P

☐

Other



**30210 0020** LOGIC 190 ANTI VANDAL SCREWS 2 PCS

☐

Notes: