




MULTINOVA 30 PIVOT 930 ADM
DIM5

27935 9305 W

AVAILABLE IN
NOIR 27935 9305 B
BLANC 27935 9305 W



 [View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Rail Monté sur rail
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
ADJUSTABILITY	0° à 45° inclinable, 360° rotatif
INFORMATION	INCL.PC SBL 3F MULTI DIMMABLE POWER ADAPTER
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,9W / CRI>90 (R9: 68) / 3000K / 2174lm
RVALUES	Rf: 89 / Rg: 97
SDMC	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	2174lm // 14,9W // 146lm/W
LED TECHNICS (LUMINAIRE)	1580lm // 17,1W // 92lm/W
Requirements	
TRACK 3F DIM	

For detailed installation instructions, please consult the manual : [27935_XXX5_HAND.pdf](#)

MULTINOVA 30 PIVOT 930 ADM DIM5

27935 9305 W

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	  
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	  
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	  

Notes: