



SPY 39 LOC1 93040

32060 9330 W

AVAILABLE IN
BLACK 32060 9330 B
WHITE 32060 9330 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 500mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male yellow

Electrical info

CLASS	III
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	883lm // 9,9W // 89lm/W

Requirements

LED POWER SUPPLY SET LOC SERIES
 SPY 39 TUBE

Options

CONNECTING CABLE LOC SERIES




For detailed installation instructions, please consult the manual : [32060_XXX0_HAND.pdf](#)

DELTALIGHT


SPY 39 LOC1 93040


32060 9330 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-
 Acoustic climate-control ceiling Interlu WEC	-

FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
<p> # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</p>	
	Min current Max current



32010 0065 EMERGENCY UNIT 1h LOC SERIES DIM5

Dimtype: DALI

1

Current supply



32010 0200 T CONNECTOR LOC SERIES



32010 0310 CONNECTING CABLE LOC SERIES 1m



32010 0320 CONNECTING CABLE LOC SERIES 2m



32010 0330 CONNECTING CABLE LOC SERIES 3m

DELTALIGHT

SPY 39 LOC1 93040

32060 9330 W



32010 0340 CONNECTING CABLE LOC SERIES 4m



32010 0350 CONNECTING CABLE LOC SERIES 5m

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0015 LED POWER SUPPLY SET LOC SERIES 500mA / 25W DIM5

1

Dimtype: DALI



32010 0025 LED POWER SUPPLY SET LOC SERIES 500mA / 35W DIM5

3

Dimtype: DALI


Finish your product

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



24144 0010 B SPY 39 TUBE B

2

24144 0010 FBR SPY 39 TUBE FBR

2

24144 0010 FG SPY 39 TUBE FG

2

24144 0010 GC SPY 39 TUBE GC

2

24144 0010 W SPY 39 TUBE W

2

DELTALIGHT

SPY 39 LOCI 93040

32060 9330 W

Notes: