




SOLI - 66 92745 MDL

REFERENCE 27121 9230 W

AVAILABLE IN
BLACK 27121 9230 B
WHITE 27121 9230 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 30° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21W / CRI>90 (R9: 60) / 2700K / 2356lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2356lm // 21W // 112lm/W
LED TECHNICS (LUMINAIRE)	1617lm // 24,2W // 67lm/W

Requirements	
SPY 66 TUBE	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

Accessories	
HONEYCOMB 57	
SPREAD LENS 57	
LINEAR SPREAD LENS 57	
SOFTENING LENS 57	
GLASS SBL 57	

For detailed installation instructions, please consult the manual : [27121_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

8

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

8


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

4


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

10

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

4


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SOLI - 66 92745 MDL

27121 9230 W




21012 0240 LED POWER SUPPLY 48V-DC / 200W

8 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 40

Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B

☐




24611 0160 GLASS SBL 57

☐




24611 0170 LINEAR SPREAD LENS 57

☐




24611 0190 SOFTENING LENS 57

☐



24611 0200 SPREAD LENS 57


☐



24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

DELTALIGHT

SOLI - 66 92745 MDL



27121 9230 W

24611 0100 FG	SPY 66 TUBE FG	☐
24611 0100 GC	SPY 66 TUBE GC	☐
24611 0100 W	SPY 66 TUBE W	☐

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐
	24611 0240 SPY 66 REFLECTOR 45°	☐

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 27111 0020 SOLI - PROFILE 2m	☒ ☐
 27111 0030 SOLI - PROFILE 3m	☒ ☐

Notes: