



OML50 - LED ARRAY DU HE 1312mm EM-3H 930

31222 9300

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
INFORMATION	CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%

Electrical info

ELECTRICAL CLASS	220-240V / 0 50-60Hz
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3648lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3648lm // 22,3W // 164lm/W UP: 2534lm // 16,3W // 155lm/W

Notes: