





MONTUR S P 30 LED 927

232 432 92 N

AVAILABLE IN
BLACK 232 432 92 B
ANTHRACITE 232 432 92 N



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	3.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6,3W / CRI>90 (R9: 50) / 2700K / 877lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	877lm // 6,3W // 139lm/W
LED TECHNICS (LUMINAIRE)	526lm // 7,2W // 73lm/W


Options

PLATE 3
 CBOX
 IP68 CONNECTION KIT
 IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [232_432_XX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 02 03 PLATE 3

☐

Notes: