





SPY 39 TRIMLESS IN SOFT 93020

24181 9020 PB

- AVAILABLE IN
- BLACK 24181 9020 B
  - BRUSHED ALU 24181 9020 BRA
  - BRUSHED ANTHRACITE 24181 9020 BRAT
  - BRUSHED COPPER 24181 9020 BRCU
  - BRUSHED GOLD 24181 9020 BRG
  - BRUSHED OLD BRONZE 24181 9020 BROB
  - FLEMISH BRONZE 24181 9020 FBR
  - FLEMISH GOLD 24181 9020 FG
  - FULL WHITE 24181 9020 FW
  - GOLD COLOURED 24181 9020 GC
  - PIANO BLACK 24181 9020 PB
  - WHITE 24181 9020 W



[View on website](#)



| General info                |                                                             |
|-----------------------------|-------------------------------------------------------------|
| LOCATION                    | indoor                                                      |
| INSTALLATION                | Ceiling Recessed                                            |
| CUTOUT SHAPE/SIZE (MM)      | round - Ø KIT                                               |
| RECESSED DEPTH (MM)         | 130                                                         |
| INGRESS PROTECTION          | IP20                                                        |
| WEIGHT (KG)                 | 0.4                                                         |
| ADJUSTABILITY               | 0° to 85° swiveling, 355° rotatable                         |
| INFORMATION                 | REFLECTOR FL-20°<br>EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC |
| Electrical info             |                                                             |
| CLASS                       | III                                                         |
| DIM TYPE                    | depending on power supply                                   |
| ENERGY CLASS                | F                                                           |
| CERTIFICATES                | CB, ENEC                                                    |
| Lightsource info            |                                                             |
| LIGHTSOURCE NAME            | LED                                                         |
| LIGHTSOURCE                 | LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm        |
| TM-30 VALUES                | rf: 90 / Rg: 99                                             |
| SDCM                        | SDCM2                                                       |
| RISKGROUP                   | RG1                                                         |
| LM80                        | L90B10 > 50000                                              |
| BEAMANGLE                   | 20°                                                         |
| LED TECHNICS (LIGHT SOURCE) | 623lm // 6W // 105lm/W                                      |
| LED TECHNICS (LUMINAIRE)    | 508lm // 6,9W // 74lm/W                                     |

| Requirements                           |  |
|----------------------------------------|--|
| SPY 39 TUBE                            |  |
| MOUNTING KIT SPY 39 TRIMLESS IN        |  |
| LED POWER SUPPLY 350mA-DC DIM (Remote) |  |

# DELTALIGHT

## SPY 39 TRIMLESS IN SOFT 93020

24181 9020 PB


For detailed installation instructions, please consult the manual : [24181\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

| Ceiling Type                                                                                                         | Mounting Kit                                                                                                                     |          |
|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------|
|  <b>System ceiling</b>               |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN   | Required |
|  <b>Plasterboard</b>                 |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN   | Required |
|  <b>Stucanet</b>                     |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN   | Required |
|  <b>Concrete + plaster</b>           |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN   | Required |
|  <b>Lintel + plaster</b>            |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN | Required |
|  <b>Hollow-core slab + plaster</b> |  24144 0050 - MOUNTING KIT SPY 39 TRIMLESS IN | Required |

### FINISH YOUR SPECIFICATION

#### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐

Cutout dimension (mm): 27

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐

#### LED power supplies

#### # of Fixtures









# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current









SPY 39 TRIMLESS IN SOFT 93020

24181 9020 PB

|                                                                                    |                                                                          |         |                          |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------|--------------------------|
|    | <b>300 48 350 ED1</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V                                                           |         |                          |
|                                                                                    | Cutout dimension (mm): 30                                                |         |                          |
|    | <b>300 48 350 ED5</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |         |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |         |                          |
|    | <b>300 48 350 MDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL  | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: non-dimmable                                                    |         |                          |
|                                                                                    | Cutout dimension (mm): 30                                                |         |                          |
|    | <b>300 48 350 WDL</b> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL  | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: WDL = wireless dimmable                                         |         |                          |
|                                                                                    | Cutout dimension (mm): 45                                                |         |                          |
|  | <b>300 90 61</b> LED POWER SUPPLY MULTI-POWER DIM6                       | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: mains (phase cut-off) or push button                            |         |                          |
|                                                                                    | Cutout dimension (mm): 56                                                |         |                          |
|  | <b>300 90 63</b> LED POWER SUPPLY MULTI-POWER DIM9                       | 4(4)    | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |         |                          |
|                                                                                    | Cutout dimension (mm): 82                                                |         |                          |
|  | <b>300 90 64</b> LED POWER SUPPLY MULTI-POWER DIM7                       | 3(2)    | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or push button                                            |         |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |         |                          |
|  | <b>300 90 67</b> LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9    | 2       | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |         |                          |
|  | <b>300 90 68</b> LED POWER SUPPLY MULTI-POWER DIM5                       | 2(2)    | <input type="checkbox"/> |
|                                                                                    | Dimtype: DALI                                                            |         |                          |
|                                                                                    | Cutout dimension (mm): 72                                                |         |                          |
|  | <b>300 90 69</b> LED POWER SUPPLY MULTI-POWER HV DIM9                    | 2->6(6) | <input type="checkbox"/> |
|                                                                                    | Dimtype: 1-10V or DALI or push button                                    |         |                          |
|                                                                                    | Cutout dimension (mm): 84                                                |         |                          |

SPY 39 TRIMLESS IN SOFT 93020

24181 9020 PB

|                                                                                     |                                                                                                                                             |      |                          |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|------|--------------------------|
|     | <b>300 90 124</b><br>LED POWER SUPPLY MULTI-POWER DIM7<br><br>Dimtype: 1-10V or push button<br><br>Cutout dimension (mm): 55                | 2(2) | <input type="checkbox"/> |
|     | <b>300 90 125</b><br>LED POWER SUPPLY MULTI-POWER MINI DIM5<br><br>Dimtype: DALI<br><br>Cutout dimension (mm): 55                           | 2(2) | <input type="checkbox"/> |
|    | <b>21012 0021</b><br>LED POWER SUPPLY MULTI POWER DIM1<br><br>Dimtype: 1-10V<br><br>Cutout dimension (mm): 54                               | 3    | <input type="checkbox"/> |
|    | <b>21012 0035</b><br>LED POWER SUPPLY MULTI POWER DIM5<br><br>Dimtype: DALI<br><br>Cutout dimension (mm): 54                                | 3    | <input type="checkbox"/> |
|   | <b>21012 004W</b><br>LED POWER SUPPLY MULTI-POWER WDL<br><br>Dimtype: WDL = wireless dimmable<br><br>Cutout dimension (mm): 84              | 4(4) | <input type="checkbox"/> |
|   | <b>21012 005W</b><br>LED POWER SUPPLY MULTI-POWER COMPACT WDL<br><br>Dimtype: WDL = wireless dimmable<br><br>Cutout dimension (mm): 54      | 3    | <input type="checkbox"/> |
|   | <b>21012 0268</b><br>LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8<br><br>Dimtype: mains (phase cut-off)<br><br>Cutout dimension (mm): 50 | 2->2 | <input type="checkbox"/> |
|   | <b>21012 0298</b><br>LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8<br><br>Dimtype: mains (phase cut-off)<br><br>Cutout dimension (mm): 48 | 2    | <input type="checkbox"/> |
|  | <b>21012 0308</b><br>LED POWER SUPPLY 350mA / 7,35W DIM8<br><br>Dimtype: mains (phase cut-off)<br><br>Cutout dimension (mm): 40             | 1    | <input type="checkbox"/> |
|   | <b>21032 0295</b><br>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5<br><br>Dimtype: DALI<br><br>Cutout dimension (mm): 30               | 2    | <input type="checkbox"/> |

# DELTALIGHT

## SPY 39 TRIMLESS IN SOFT 93020

24181 9020 PB

### Mounting kits




**24144 0050** MOUNTING KIT SPY 39 TRIMLESS IN

Cutout dimension (mm): 82

☐

### Finish your product



**24144 0010 B** SPY 39 TUBE B

☐

**24144 0010 FBR** SPY 39 TUBE FBR

☐

**24144 0010 FG** SPY 39 TUBE FG

☐

**24144 0010 GC** SPY 39 TUBE GC

☐

**24144 0010 W** SPY 39 TUBE W

☐



**24144 0070** SPY 39 TUBE SBL

☐

Notes: