



M26L - SPY 391 93020 MDL

23258 9320 BRA

AVAILABLE IN

NOIR 23258 9320 B

ALU BROSSÉ 23258 9320 BRA

ANTHRACITE BROSSÉ 23258 9320 BRAT

CUIVRE BROSSÉ 23258 9320 BRCU

OR BROSSÉ 23258 9320 BRG

BRONZE VIEUX BROSSÉ 23258 9320 BROB


FLEMISH BRONZE 23258 9320 FBR

FLEMISH GOLD 23258 9320 FG

COULEUR OR 23258 9320 GC

NOIR PIANO 23258 9320 PB

BLANC 23258 9320 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 85° inclinable, 360° rotatif
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = dimmable 1 à 10 V ou DALI ou bouton poussoir
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23258_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

le cable d'alimentation

of Fixtures

 web2print_power_supply_info_box

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19


Dimtype: WDL = dimmable sans fil

SMART 48

of Fixtures

 web2print_power_supply_info_box


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 012 SMART 48 MODULATOR WD

19


Dimtype: WDL = dimmable sans fil

les alimentations led

of Fixtures

 web2print_power_supply_info_box


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non dimmable


DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 BRA

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	10	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	20	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 40		

modifier les dispositifs de lumière

	24144 0030 B VISOR 39 B	☐
--	--------------------------------	--------------------------

Terminez votre produit

	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FG SPY 39 TUBE FG	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐

DELTALIGHT


M26L - SPY 391 93020 MDL

23258 9320 BRA

COMPATIBLE COMPOSABLES





SHIFTLINE M26L FLOOR

Available Colours

	29321 0010 SLM26L F MDL	
	29322 002W SLM26L F MDL WD	




SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours

	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         

SHIFTLINE M35R profile


Available Colours

	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 BRA



23375 0030 SLM35R - PROFILE 3m



Notes: