



## SPY 39 LOC1 94040

32060 9430 W

AVAILABLE IN  
**BLACK** 32060 9430 B  
**WHITE** 32060 9430 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 355° rotatable
<b>INFORMATION</b>	EXCL.LED POWER SUPPLY 500mA-DC INCL.1 x CABLE 2 x 0,75mm <sup>2</sup> - 0,5m + WIELAND PLUG GST08i2 male yellow

### Electrical info

<b>CLASS</b>	III
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 79) / 4000K / 1152lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1152lm // 8,6W // 134lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	934lm // 9,9W // 94lm/W

### Requirements

LED POWER SUPPLY SET LOC SERIES  
 SPY 39 TUBE

### Options

CONNECTING CABLE LOC SERIES




For detailed installation instructions, please consult the manual : [32060\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## SPY 39 LOCI 94040

32060 9430 W

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-
 Acoustic climate-control ceiling Interlu WEC	-

### FINISH YOUR SPECIFICATION


#### Emergency units

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**32010 0065** EMERGENCY UNIT 1h LOC SERIES DIM5

Dimtype: DALI

1

#### Current supply



**32010 0200** T CONNECTOR LOC SERIES



**32010 0310** CONNECTING CABLE LOC SERIES 1m



**32010 0320** CONNECTING CABLE LOC SERIES 2m



**32010 0330** CONNECTING CABLE LOC SERIES 3m

# DELTALIGHT

## SPY 39 LOC1 94040

32060 9430 W



**32010 0340** CONNECTING CABLE LOC SERIES 4m



**32010 0350** CONNECTING CABLE LOC SERIES 5m


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**32010 0015** LED POWER SUPPLY SET LOC SERIES 500mA / 25W DIM5

1

Dimtype: DALI



**32010 0025** LED POWER SUPPLY SET LOC SERIES 500mA / 35W DIM5

3

Dimtype: DALI


### Finish your product

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**24144 0010 B** SPY 39 TUBE B

2

**24144 0010 FBR** SPY 39 TUBE FBR

2

**24144 0010 FG** SPY 39 TUBE FG

2

**24144 0010 GC** SPY 39 TUBE GC

2

**24144 0010 W** SPY 39 TUBE W

2

# DELTALIGHT

## **SPY 39 LOCI 94040**

32060 9430 W

Notes: