





D-LINER 30 INF LOC2 838 93058 DIM5

32083 9325 B-B

AVAILABLE IN

BLACK-BLACK 32083 9325 B-B

WHITE-WHITE 32083 9325 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-58° INCL.DIMMABLE LED POWER SUPPLY 390mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 13W / CRI>90 / 3000K / 2293lm
LED TECHNICS (LIGHT SOURCE)	2293lm // 13W // 177lm/W
LED TECHNICS (LUMINAIRE)	1814lm // 15W // 121lm/W

For detailed installation instructions, please consult the manual : [32083_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Hunter Douglas 30BD

DELTALIGHT

D-LINER 30 INF LOC2 838 93058 DIM5

32083 9325 B-B

Notes: