





M26L - SPY 391 93020 MDL

REFERENCE

23258 9320 BRAT

AVAILABLE IN

BLACK 23258 9320 B
BRUSHED ALU 23258 9320 BRA
BRUSHED ANTHRACITE 23258 9320 BRAT
BRUSHED COPPER 23258 9320 BRCU
BRUSHED GOLD 23258 9320 BRG
BRUSHED OLD BRONZE 23258 9320 BROB
FLEMISH BRONZE 23258 9320 FBR
FLEMISH GOLD 23258 9320 FG
GOLD COLOURED 23258 9320 GC
PIANO BLACK 23258 9320 PB
WHITE 23258 9320 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39
 LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23258_XXX0_HAND.pdf](#)




FINISH YOUR SPECIFICATION

Current supply		# of Fixtures
		Min current Max current
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		
1639190 21032 0030 SMART 48 MODULATOR PLUG-IN WD Dimtype: WDL = wireless dimmable	19	
SMART 48		# of Fixtures
		Min current Max current
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		
569378 300 90 011 SMART 48 MODULATOR DIM9 Dimtype: 1-10V or DALI or push button	19	
569378 300 90 012 SMART 48 MODULATOR WD Dimtype: WDL = wireless dimmable	19	
LED power supplies		# of Fixtures
		Min current Max current
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	10	


DELTALIGHT

M26L - SPY 391 93020 MDL


23258 9320 BRAT

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	24	☐
	Dimtype: non-dimmable		
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	10	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	20	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		

Light altering devices

	24144 0030 B VISOR 39 B		☐
---	--------------------------------	--	--------------------------

Finish your product










	24144 0010 B SPY 39 TUBE B		☐
	24144 0010 FBR SPY 39 TUBE FBR		☐
	24144 0010 FC SPY 39 TUBE FC		☐
	24144 0010 GC SPY 39 TUBE GC		☐
	24144 0010 W SPY 39 TUBE W		☐
	24144 0070 SPY 39 TUBE SBL		☐

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 BRAT


COMPATIBLE COMPOSABLES

SHIFTLINE M26L FLOOR		Available Colours
	29321 0010 SLM26L F MDL	
	29322 002W SLM26L F MDL WD	
SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         
SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 BRAT



23375 0030 SLM35R - PROFILE 3m

Notes: