DELTALIGHT



Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 180 DOWN-UP 93063 DIM5

REFERENCE 30723 9335 B-B

AVAILABLE IN
BLACK-BLACK 30723 9335 B-B
WHITE-BLACK 30723 9335 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver DALI DT6 : DOWN & UP on separate channels INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm² 1,6m

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN (HO): 3494lm // 24,2W // 145lm/W UP (HO): 3494lm // 24,2W // 145lm/W Or DOWN: 2534lm // 16,3W // 155lm/W UP: 2534lm // 16,3W // 155lm/W
LED TECHNICS (LUMINAIRE)	DOWN (HO): 2417lm // 28W // 87lm/W UP (HO): 2301lm // 28W // 83lm/W Or DOWN: 1753lm // 19W // 94lm/W UP: 1669lm // 19W // 89lm/W

Options

CABLE BASE R / S

DELTALIGHT

INFORM 40 SQ 180 DOWN-UP 93063 DIM5

30723 9335 B-B

For detailed installation instructions, please consult the manual : **30723_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Notes: