





COMPO S WALLWASH SOFT 930

9 15716 9000 C

AVAILABLE IN

CHROME 9 15716 9000 C

BLANC 9 15716 9000 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.12
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	236lm // 6,9W // 34lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

For detailed installation instructions, please consult the manual : [9_15716_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1 ☐
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1 ☐
15710 5100	LED POWER SUPPLY MULTIPOWER 8W DALI DT6 350mA	1 ☐
Dimtype: DALI		

kit de montage	
	15710 0010 B MOUNTING KIT COMPO S TRIM B ☐
Cutout dimension (mm): 55	
	15710 0010 W MOUNTING KIT COMPO S TRIM W ☐
	15710 0040 MOUNTING KIT COMPO S TRIMLESS ☐
Cutout dimension (mm): 55	

DELTALIGHT

COMPO S WALLWASH SOFT 930

9 15716 9000 C

Notes: