





COMPO S WALLWASH SOFT 930

9 15716 9000 C

AVAILABLE IN

CHROM 9 15716 9000 C

WEISS 9 15716 9000 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Decke Einbau
CUTOUT SHAPE/SIZE (MM)	rund - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.12
ADJUSTABILITY	0° to 30° schwenkbar, 355° drehbar

Electrical info

CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	236lm // 6,9W // 34lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

For detailed installation instructions, please consult the manual : [9_15716_XXX0_HAND.pdf](#)

COMPO S WALLWASH SOFT 930

9 15716 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 Plasterboard	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 Wood	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Netzteil

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3800

LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA

1

15710 4500

LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA

1

15710 5100

LED POWER SUPPLY MULTIPOWER 8W DALI DT6 350mA

1

Dimtype: DALI

Mounting Kit



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W



15710 0040 MOUNTING KIT COMPO S TRIMLESS

Cutout dimension (mm): 55

DELTALIGHT

COMPO S WALLWASH SOFT 930

9 15716 9000 C

Notes: