





SPY 66 LOC1 93045

32061 9330 B

AVAILABLE IN
BLACK 32061 9330 B
WHITE 32061 9330 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 700mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male yellow

Electrical info	
CLASS	III
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2811lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	1929lm // 28,8W // 67lm/W

Requirements	
LED POWER SUPPLY SET LOC SERIES SPY 66 TUBE	

Options	
CONNECTING CABLE LOC SERIES	


For detailed installation instructions, please consult the manual : [32061_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interalu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-
 Acoustic climate-control ceiling Interalu WEC	-

FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	32010 0065 EMERGENCY UNIT 1h LOC SERIES DIM5	1 ☐
Dimtype: DALI		

Current supply		
	32010 0200 T CONNECTOR LOC SERIES	☐
	32010 0310 CONNECTING CABLE LOC SERIES 1m	☐
	32010 0320 CONNECTING CABLE LOC SERIES 2m	☐
	32010 0330 CONNECTING CABLE LOC SERIES 3m	☐

DELTALIGHT

SPY 66 LOC1 93045

32061 9330 B



32010 0340 CONNECTING CABLE LOC SERIES 4m

☐

32010 0350 CONNECTING CABLE LOC SERIES 5m

☐


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




32010 0035 LED POWER SUPPLY SET LOC SERIES 700mA / 25W DIM5

1

☐

Dimtype: DALI



32010 0045 LED POWER SUPPLY SET LOC SERIES 700mA / 50W DIM5

2

☐

Dimtype: DALI


Finish your product

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



24611 0100 B SPY 66 TUBE B

3

☐

24611 0100 FBR SPY 66 TUBE FBR

3

☐

24611 0100 FG SPY 66 TUBE FG

3

☐

24611 0100 GC SPY 66 TUBE GC

3

☐

24611 0100 W SPY 66 TUBE W

3

☐

DELTALIGHT

SPY 66 LOC1 93045

32061 9330 B

Notes: