



ENTERO SQ-S X TW 96520

28541 9020 FW



AVAILABLE IN

BLACK 28541 9020 B

FLEMISH BRONZE OUTDOOR 28541 9020 FBRX

FULL WHITE 28541 9020 FW

ANTHRACITE 28541 9020 N



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	110
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.285
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	658lm // 10,4W // 64lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Accessories


ENTERO S HONEYCOMB
ENTERO S LINEAR SPREAD LENS
ENTERO S SPREAD LENS
ENTERO S SOFTENING LENS
ENTERO S GLASS SBL

For detailed installation instructions, please consult the manual : [28541_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2
Light altering devices		
	28500 0010 ENTERO S LINEAR SPREAD LENS	

DELTALIGHT

ENTERO SQ-S X TW 96520


28541 9020 FW




28500 0020 ENTERO S SPREAD LENS

☐

28500 0030 ENTERO S SOFTENING LENS

☐

28500 0040 ENTERO S GLASS SBL

☐

28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: