





SUPERDOME 9528 RECESSED DIM1

321 96 9528 ED1 W-W

AVAILABLE IN

BLACK-WHITE 321 96 9528 ED1 B-W

WHITE-WHITE 321 96 9528 ED1 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	350
INGRESS PROTECTION	IP20
WEIGHT (KG)	27
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL FIX ANGLE 10° INCL.2 x LED POWER SUPPLY 350mA

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 105W / CRI>90 / 3000K / 16950lm
LED TECHNICS (LIGHT SOURCE)	16950lm // 105W // 161lm/W
LED TECHNICS (LUMINAIRE)	13043lm // 120,8W // 108lm/W

Requirements

SUPERDOME RECESSED KIT

For detailed installation instructions, please consult the manual : [321_96_9528_ED1_HAND.pdf](#)

SUPERDOME 9528 RECESSED DIM1



321 96 9528 ED1 W-W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	Plasterboard  321 96 1036 - SUPERDOME RECESSED KIT Required
	Stucanet  321 96 1036 - SUPERDOME RECESSED KIT Required

FINISH YOUR SPECIFICATION

Miscellaneous control equipment

	300 90 016 ED1 WIRELESS CONTROL 5A DIM1 ☐
Dimtype: WDL = wireless dimmable	
Cutout dimension (mm): 86	
	385 611 ED5 DALI TO 1-10V CONVERTER ☐
Dimtype: DALI	

Recessed kits

	321 96 1036 SUPERDOME RECESSED KIT ☐
Cutout dimension (mm): 1105 x 1105	

Notes: