





DOT.COM ON WALLWASH 12 HO 930

REFERENCE 16315 9300 B

AVAILABLE IN
BLACK 16315 9300 B
WHITE 16315 9300 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 700mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 25,2W / CRI>90 (R9: 60) / 3000K / 3000lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3000lm // 25,2W // 119lm/W
LED TECHNICS (LUMINAIRE)	1738lm // 29W // 60lm/W
Requirements	
LED POWER SUPPLY 700mA-DC DIM	

For detailed installation instructions, please consult the manual : [16315_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 700 ED1

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 700 ED5

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




300 48 700 MDL

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL

1

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 700 PRO ED1

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 700 PRO ED5

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5

1

Dimtype: DALI

Cutout dimension (mm): 45




300 48 700 PRO WDL

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 48 700 WDL

LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL

1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61

LED POWER SUPPLY MULTI-POWER DIM6











1

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56





DOT.COM ON WALLWASH 12 HO 930

16315 9300 B

	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	2(1)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(0)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(0)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	2(1)	☐

DOT.COM ON WALLWASH 12 HO 930

16315 9300 B

	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1	☐
	<u>21012 0288</u> LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1	☐
	<u>21032 0315</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1	☐
	<u>21032 0385</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 Dimtype: DALI Cutout dimension (mm): 30	1	☐

Notes: