



CUPPA C SOFT 93040



REFERENCE

28816 9030 B-GC

AVAILABLE IN

NOIR-COULEUR OR 28816 9030 B-GC

BLANC-COULEUR OR 28816 9030 W-GC



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WFL-40° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m
Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	795lm // 11,7W // 68lm/W

Remarks

Black cable for B-GC version and grey cable for W-GC version

Requirements

CUPPA SHADE

LASS-OH! POWERBOX

LED POWER SUPPLY 350 / 500mA-DC DIM

Options

CONNECTION TRIMLESS








CEILING BASE R

CEILING BASE MULTI 1

CEILING BASE MULTI 3

For detailed installation instructions, please consult the manual : [28816_XXX0_HAND.pdf](#)










FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
web2print_power_supply_info_box			Min current Max current
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2 ☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 30		
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2 ☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2 ☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		
	300 48 500 WDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2 ☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 45		
	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	2 ☐
	Dimtype: fin de phase ou bouton poussoir		
	Cutout dimension (mm): 56		
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	3(3) ☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	Cutout dimension (mm): 82		
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	2(1) ☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 72		

DELTALIGHT

CUPPA C SOFT 93040


28816 9030 B-GC

	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(1) ☐
	Dimtype: DALI	
	Cutout dimension (mm): 72	
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	5(3) ☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir	
	Cutout dimension (mm): 84	
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	1(1) ☐
	Dimtype: 1 à 10 V ou bouton poussoir	
	Cutout dimension (mm): 55	
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) ☐
	Dimtype: DALI	
	Cutout dimension (mm): 55	
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER	2 ☐
	Dimtype: non dimmable	
	Cutout dimension (mm): 50	
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	2 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 54	
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	2 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 54	
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	3(3) ☐
	Dimtype: WDL = dimmable sans fil	
	Cutout dimension (mm): 84	
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	2 ☐
	Dimtype: WDL = dimmable sans fil	
	Cutout dimension (mm): 54	
	<u>21012 0278</u> LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 ☐
	Dimtype: fin de phase	
	Cutout dimension (mm): 55	

DELTALIGHT

CUPPA C SOFT 93040

28816 9030 B-GC



21012 0288


LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2



Dimtype: fin de phase

Cutout dimension (mm): 55



21012 0298


LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1



Dimtype: fin de phase

Cutout dimension (mm): 48



21032 0305

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30

Power box



24814 0075 B LASS-OH! POWERBOX H15 DIM5 B



Dimtype: DALI




24814 0080 B LASS-OH! POWERBOX H15 B



Dimtype: non dimmable


les accessoires de suspension



15229 0010 B CABLE CLAMP B



les accessoires pour connexions électriques



328 10 03 CONNECTION TRIMLESS O.F.A.





Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT


CUPPA C SOFT 93040

28816 9030 B-GC

Terminez votre produit

	<u>28800 0010 B</u>	CUPPA SHADE 120 B	☐
	<u>28800 0010 GC</u>	CUPPA SHADE 120 GC	☐
	<u>28800 0010 W</u>	CUPPA SHADE 120 W	☐
	<u>28800 0020 B</u>	CUPPA SHADE 190 B	☐
	<u>28800 0020 GC</u>	CUPPA SHADE 190 GC	☐
	<u>28800 0020 W</u>	CUPPA SHADE 190 W	☐
	<u>28800 0030 B</u>	CUPPA SHADE 300 B	☐
	<u>28800 0030 GC</u>	CUPPA SHADE 300 GC	☐
	<u>28800 0030 W</u>	CUPPA SHADE 300 W	☐
	<u>28800 0040 B</u>	CUPPA DISK B	☐
	<u>28800 0040 W</u>	CUPPA DISK W	☐

Bases de plafond

	<u>23943 0010 B</u>	CEILING BASE R B	☐
--	----------------------------	------------------	--------------------------

DELTALIGHT

CUPPA C SOFT 93040


28816 9030 B-GC



28700 0040 B CEILING BASE MULTI 1 B

☐

28700 0040 W CEILING BASE MULTI 1 W

☐

28700 0070 B CEILING BASE MULTI 3 B

☐

28700 0070 W CEILING BASE MULTI 3 W

☐

Notes: