

**OML50 - PRISMATIC LENS D TW
CORNER R420 90° 950 DIM5**

31657 9005 B

BESCHIKBAAR IN
ZWART 31657 9005 B[Bekijk op website](#)**Algemene info**

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	10
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 12W / CRI>90 (R9: 50) / 2700K-5000K / 1604lm Or @ 5000K: LED cluster 11W / CRI>90 (R9: 50) / 2700K-5000K / 1912lm
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	@ 2700K: 1604lm // 12W // 134lm/W Or @ 5000K: 1912lm // 11W // 174lm/W

Opties

WIRELESS CONTROL DIM5

Notes: