

OML50 - PRISMATIC LENS D TW
CORNER R420 90° 950 DIM5

31657 9005 B

AVAILABLE IN
BLACK 31657 9005 B

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	10
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 12W / CRI>90 (R9: 50) / 2700K-5000K / 1604lm Or @ 5000K: LED cluster 11W / CRI>90 (R9: 50) / 2700K-5000K / 1912lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 1604lm // 12W // 134lm/W Or @ 5000K: 1912lm // 11W // 174lm/W
Options	
WIRELESS CONTROL DIM5	

Notes: