



HALOSCAN ON 1 MP SOFT 93035 DIM8



23148 9038 B-B

AVAILABLE IN

BLACK-BLACK 23148 9038 B-B

BLACK-GOLD COLORED 23148 9038 B-GC

WHITE-WHITE 23148 9038 W-W



[View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Ceiling Surface mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.5 |
| ADJUSTABILITY | 0° to 45° swiveling, 355° rotatable |
| INFORMATION | LENS FL-35° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC |

Electrical info

| | |
|-------------------------|-----------------------|
| ELECTRICAL CLASS | 220-240V / 50-60Hz |
| POWER SUPPLY | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | E |
| CERTIFICATES | CB, ENEC, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm |
| TM-30 VALUES | rf: 90 / Rg: 99 |
| SDCM | SDCM2 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| BEAMANGLE | 35° |
| LED TECHNICS (LIGHT SOURCE) | 623lm // 6W // 105lm/W |
| LED TECHNICS (LUMINAIRE) | 478lm // 6,9W // 69lm/W |

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23148_XXX8_HAND.pdf](#)


DELTALIGHT

HALOSCAN ON 1 MP SOFT 93035 DIM8

23148 9038 B-B


FINISH YOUR SPECIFICATION

Light altering devices




23110 0040

HALOSCAN LINEAR SPREAD LENS



23110 0050 B

HALOSCAN HONEYCOMB B



23110 0060 B

HALOSCAN KAP MP B

23110 0060 W

HALOSCAN KAP MP W

Notes: