DELTALIGHT



OML50 - LED ARRAY DU HE 1312mm EM-3H 940

REFERENCE 31222 9400

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
INFORMATION	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT INCL.EMERGENCY UNIT 3H / BLF xx%

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,3W / CRI>90 (R9: 50) / 4000K / 3802lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3802lm // 22,3W // 171lm/W UP: 2643lm // 16,3W // 162lm/W

Notes: