





SPY 66 LOC1 94045

REFERENCE 32061 9430 W

AVAILABLE IN
BLACK 32061 9430 B
WHITE 32061 9430 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 700mA-DC INCL.1 x CABLE 2 x 0,75mm² - 0,5m + WIELAND PLUG GST08i2 male yellow

Electrical info	
CLASS	III
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 79) / 4000K / 2974lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2974lm // 25W // 119lm/W
LED TECHNICS (LUMINAIRE)	2041lm // 28,8W // 71lm/W

Requirements	
LED POWER SUPPLY SET LOC SERIES SPY 66 TUBE	

Options	
CONNECTING CABLE LOC SERIES	

For detailed installation instructions, please consult the manual : [32061_XXX0_HAND.pdf](#)

DELTALIGHT

SPY 66 LOC1 94045

32061 9430 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-
 Acoustic climate-control ceiling Interlu WEC	-

FINISH YOUR SPECIFICATION


Emergency units

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0065 EMERGENCY UNIT 1h LOC SERIES DIM5

Dimtype: DALI

1

Current supply



32010 0200 T CONNECTOR LOC SERIES



32010 0310 CONNECTING CABLE LOC SERIES 1m



32010 0320 CONNECTING CABLE LOC SERIES 2m



32010 0330 CONNECTING CABLE LOC SERIES 3m

DELTALIGHT

SPY 66 LOC1 94045

32061 9430 W



32010 0340 CONNECTING CABLE LOC SERIES 4m

☐

32010 0350 CONNECTING CABLE LOC SERIES 5m

☐


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




32010 0035 LED POWER SUPPLY SET LOC SERIES 700mA / 25W DIM5

1

☐

Dimtype: DALI



32010 0045 LED POWER SUPPLY SET LOC SERIES 700mA / 50W DIM5

2

☐

Dimtype: DALI

Finish your product

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



24611 0100 B SPY 66 TUBE B

3

☐

24611 0100 FBR SPY 66 TUBE FBR

3

☐

24611 0100 FG SPY 66 TUBE FG

3

☐

24611 0100 GC SPY 66 TUBE GC

3

☐

24611 0100 W SPY 66 TUBE W

3

☐

DELTALIGHT

SPY 66 LOC1 94045

32061 9430 W

Notes: