



SUPERLOOP SLIM OUT 70 SBL 930

20576 9300 W

AVAILABLE IN


NOIR 20576 9300 B

FLEMISH BRONZE 20576 9300 FBR

FLEMISH GOLD 20576 9300 FG

COULEUR OR 20576 9300 GC

BLANC 20576 9300 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 500-700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,2-29,2W / CRI>90 (R9: 59) / 3000K / 2916-3870lm
SDMC	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3870lm // 29,2W // 132lm/W
LED TECHNICS (LUMINAIRE)	1713lm // 33,6W // 51lm/W

Requirements

LED POWER SUPPLY 500 / 700mA-DC DIM
SUPERLOOP POWERBOX L 500mA
SUPERLOOP POWERBOX L/H 700mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20576_XXX0_HAND.pdf](#)


DELTA LIGHT

SUPERLOOP SLIM OUT 70 SBL 930

20576 9300 W




FINISH YOUR SPECIFICATION

le cable d'alimentation

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

les alimentations led







of Fixtures

	web2print_power_supply_info_box	Min current Max current
	300 90 127 LED POWER SUPPLY 500mA-DC / 27W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 ☐
	300 90 128 LED POWER SUPPLY 700mA-DC / 36W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 ☐
	300 90 131 LED POWER SUPPLY 700mA-DC / 38W DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 ☐






DELTALIGHT

SUPERLOOP SLIM OUT 70 SBL 930

20576 9300 W

Power box			# of Fixtures
 web2print_power_supply_info_box			Min current Max current
	<u>321 55 205 ED1 B</u>	SUPERLOOP POWERBOX L 500mA DIM1 B	1 ☐
	Dimtype: 1 à 10 V		
	<u>321 55 205 ED1 W</u>	SUPERLOOP POWERBOX L 500mA DIM1 W	1 ☐
	<u>321 55 207 ED1 B</u>	SUPERLOOP POWERBOX L 700mA DIM1 B	1 ☐
	Dimtype: 1 à 10 V		
	<u>321 55 207 ED1 W</u>	SUPERLOOP POWERBOX L 700mA DIM1 W	1 ☐
	<u>321 55 307 ED5 B</u>	SUPERLOOP POWERBOX H8 700mA DIM5 B	1 ☐
	Dimtype: DALI		
	<u>321 55 307 ED5 W</u>	SUPERLOOP POWERBOX H8 700mA DIM5 W	1 ☐

les sets pour recouvrement plafond

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐

DELTALIGHT

SUPERLOOP SLIM OUT 70 SBL 930

20576 9300 W

	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERLOOP SLIM OUT 70 SBL 930

20576 9300 W

les accessoires de suspension

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

les accessoires pour connexions électriques

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: